

## Product Data Sheet

TerraTex NO6 w/ 12.5ga 2" x 4" 24" x 100'  
Austin Spec Silt Fence (76016)

### Assembled Unit Components

Geotextile Fabric: TerraTex NO6  
Fabric Height: 36 in  
Support Wire: Welded Wire  
Height: 24"  
Gauge: 12.5 ga  
Opening Size: 2" x 4"  
Zinc Coating: Class 1  
Unit Length: 100 ft

Hanes Geo Components preassembled silt fence is TerraTex NO6 with 24" 2" x 4" 12.5 ga welded wire and is assembled in the USA. TerraTex NO6 is a non-woven geotextile made up of polypropylene fibers that are needed to form stable and durable structure, which allows the fibers to maintain their relative position. It is non-biodegradable and resistant to ultraviolet degradation, rotting, and most soil chemicals.

PROPERTY	TEST METHOD	MARV English
Tensile Strength	ASTM D4632	160 lbs.
Trapezoid Tear	ASTM D4533	65 lbs.
Elongation	ASTM D4632	50%
Puncture Resistance	ASTM D4833	90 lbs.
CBR Puncture	ASTM D6241	410 lbs.
Mullen Burst	ASTM D3786	315 psi
UV Resistance (500 hrs)	ASTM D4355	70%
Apparent Opening Size (AOS)**	ASTM D4751	70 US Std.Sieve
Permittivity	ASTM D4491	1.6 sec <sup>-1</sup>
Water Flow Rate	ASTM D4491	110 gpm/ft <sup>2</sup>

**\*DISCLAIMER:** Descriptions regarding the products described herein are based solely upon information provided by the manufacturer and are provided for informational purposes only. NOTHING CONTAINED HEREIN SHOULD BE CONSTRUED AS CREATING AN EXPRESSED OR IMPLIED WARRANTY, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS, EACH OF WHICH IS HEREBY DISCLAIMED. THERE ARE NO WARRANTIES THAT EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. The final determination as to the suitability of any product of Hanes Geo Components in any particular application rests solely with the user. Hanes Geo Components reserves the right to alter or modify its products and descriptions at any time without notice.