



980g Coir Mat

| Property | Test Method | English | Metric |
|----------------------|-------------|---------------------------|---------------------------|
| Material | | 100 coir fibre | 100 coir fibre |
| Width | | 6.5 or 13 ft | 6.5 or 13 m |
| Length | | 82 or 164 ft | 82 or 164 m |
| Thickness | ASTM D 5199 | 0.16 - 0.24 in | 4-6 mm |
| AOS | ASTM D 4751 | 0.39 x 0.47 in | 10 x 12 mm |
| Mass | ASTM D 5261 | 906 gsm | 906 gsm |
| Tensile Strength Dry | ASTM D 4595 | mc 12.00 cross 9.8 kN / m | mc 12.00 cross 9.8 kN / m |
| Elongation at Break | ASTM D 4595 | mc 38 cross 38 % | mc 38 cross 38 % |
| Grab Elongation | ASTM D 4632 | mc 27.5 cross 27.5 % | mc 27.5 cross 27.5 % |
| Open Area | Calculated | 34 % | 34 % |

DISCLAIMER: Descriptions regarding the products described herein are based solely upon information provided by the manufacturer and are provided for informational purposes only. NOTHING CONTAINED HEREIN SHOULD BE CONSTRUED AS CREATING AN EXPRESSED OR IMPLIED WARRANTY, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS, EACH OF WHICH IS HEREBY DISCLAIMED. THERE ARE NO WARRANTIES THAT EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. The final determination as to the suitability of any product of Hanes Geo Components in any particular application rests solely with the user. Hanes Geo Components reserves the right to alter or modify its products and descriptions at any time without notice.